

Page 1 of 5

## BHM100PS - MOD. PLUS G100 P/S

1. Product And Company Identification			
<u>Supplier</u> HENRY COMPANY 999 N. Sepulveda Blvd., Suite 800 El Segundo, CA 90245-2716	ManufacturerHENRY COMPANY999 N. Sepulveda Blvd., Suite 800El Segundo, CA 90245-2716Company Contact: Technical ServicesTelephone Number: (800) 486-1278Web Site: www.henry.comwww.ca.henry.comManufacturer Emergency Contacts & Phone NumberCHEMTREC: (800) 424-9300CHEMTREC: (703) 527-3887CANUTEC: (613) 996-6666		
Company Contact: Technical Services Telephone Number: (800) 486-1278 Web Site: www.henry.com www.ca.henry.com			
Supplier Emergency Contacts & Phone Number CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666			
Issue Date: 10/13/2014 Product Name: BHM100PS - MOD. PLUS G100 P/S Product Code: BHM100PS <u>Product/Material Uses</u> Roofing Membrane			
2. Composition/Information On Ingredients			
Ingredient Name	CAS	r	Percent Of Total Weight
asphalt, petroleum	8052-4	2-4	30 - 50
calcium carbonate	1317-6	5-3	25 - 35
glass fibers	65997-1	7-3	1 - 5
high density polyethylene	9002-8	8-4	1 - 5
rubber compounds	NA - Mix	ure	1 - 5
silica, quartz	14808-6	0-7	10 - 20
EMERGEN	ICY OVERVIEW		

CAUTION! This product contains asphalt. Some asphalt contains sulfur compounds which may form hydrogen sulfide when heated or burned. Prolonged direct skin and eye contact may cause irritation. Appearance/Odor: Rolled material.

3. Hazards Identification

## Primary Routes(s) Of Entry

Inhalation - possible if product becomes airborne, but considered unlikely.

### Eye Hazards

Particles may cause eye irritation.

## <u>Skin Hazards</u>

May cause skin irritation and contact dermatitis upon prolonged contact.

## Ingestion Hazards

Not a probable route of exposure.



Page 2 of 5

# BHM100PS - MOD. PLUS G100 P/S

3. Hazards Identification - Continued

## **Inhalation Hazards**

Not a probable route of exposure under normal conditions of use.

#### **Chronic/Carcinogenicity Effects**

This product or one of its ingredients present at 0.1% or more is listed as a carcinogen by NTP, IARC or OSHA. See Section 11 (Toxicological Information) for more details.

4. First Aid Measures

#### <u>Eye</u>

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

#### <u>Skin</u>

Remove contaminated clothing and shoes. Wash affected areas with soap and water.

#### Ingestion

Get medical attention immediately. DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious victim.

#### **Inhalation**

Inhalation not likely due to nature of material. If particles generated from grining or sanding are inhaled, remove the person from the contaminated area to fresh air.

5. Fire Fighting Measures

Flammability Class: Non Flammable

#### **Fire And Explosion Hazards**

During a fire carbon monoxide, carbon dioxide, oxides of nitrogen and sulfur, hydrogen sulfide, and irritating and/or toxic gases may be generated.

#### **Extinguishing Media**

Carbon dioxide, water, or dry chemical.

#### **Fire Fighting Instructions**

Firefighters should wear self-contained breathing apparatus and full protective gear.

#### 6. Accidental Release Measures

Collect and dispose in accordance with applicable regulations. Avoid release to waterways and sewers.

7. Handling And Storage

#### Handling And Storage Precautions

Keep containers tightly closed. Store in a cool, dry, well-ventilated area. Protect from heat sparks, or flame. Use only with adequate ventilation.

#### 8. Exposure Controls/Personal Protection

#### Engineering Controls

Use with adequate general and local exhaust ventilation.

#### **Eye/Face Protection**

Safety glasses with side shields recommended.

### Skin Protection

Use with protective gloves and apron to prevent skin contact.



Page 3 of 5

# BHM100PS - MOD. PLUS G100 P/S

8. Exposure Controls/Personal Protection - Continued

#### **Respiratory Protection**

None normally required. Respirator use may be required due to secondary operations such as cutting, sanding, buffing, etc. The level of respiratory protection needed should be based on the evaluation of chemical exposures by a health or safety professional.

Occupational Exposure Limits for individual ingredients (if available) are listed below.

Asphalt fume

ACGIH TLV-TWA 0.5 mg/m3 (Inhalable fraction and vapor)

#### Ingredient(s) - Exposure Limits

asphalt, petroleum OSHA PEL-TWA 5mg/m3 ACGIH TLV-TWA 0.5mg/m3 (Benzene soluble aerosol) silica, quartz ACGIH TLV-TWA 0.025 mg/m3 OSHA PEL-TWA 30mg/m3 / (%SiO2+2) (total dust) OSHA PEL-TWA 10 mg/m3/ (%SiO2+2) (respirable dust)

#### 9. Physical And Chemical Properties

Appearance Flexible sheet

Chemical Type: Mixture Physical State: Solid Boiling Point: 650-1000 °F 343-538 °C Specific Gravity: >1.0 Percent Volatiles: <0.5% Vapor Pressure: not applicable Vapor Density: not available pH Factor: not available Solubility: not available Evaporation Rate: not available

10. Stability And Reactivity

Stability: Stable Hazardous Polymerization: Not expected to occur

#### **Conditions To Avoid (Stability)**

Extreme temperatures, open flames, and strong oxidants.

#### **Hazardous Decomposition Products**

Decomposition not expected to occur if handled and stored properly.

#### **Conditions To Avoid (Polymerization)**

Incomplete combustion

11. Toxicological Information

#### Chronic/Carcinogenicity

Silica, quartz present in this product, at concentrations equal to or greater than 0.1%, has been determined to be carcinogenic as follows: IARC: Group 1, NTP:listed, OSHA: not regulated, and ACGIH: A2.



Page 4 of 5

# BHM100PS - MOD. PLUS G100 P/S

#### 11. Toxicological Information - Continued

### Miscellaneous Toxicological Information

Toxicological testing has not been conducted for this product overall. Available toxicological data for individual ingredients are summarized below.

### Ingredient(s) - Carcinogenicity

high density polyethylene Listed In The IARC Monographs silica, quartz NTP - Listed On The National Toxicology Program Listed In The IARC Monographs

#### Ingredient(s) - Toxicological Data

calcium carbonate LD50 (oral-rat) : 6450 mg/kg silica, quartz LD50 (iv-rat ): 500 mg/kg bw/Quartz (10-200 um)

#### 12. Ecological Information

None identified.

#### 13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

#### 14. Transport Information

Ground Not restricted

IMDG Not restricted

IATA Not restricted

15. Regulatory Information

#### U.S. Regulatory Information

Warning: This product contains a substance(s) known to the State of California to cause cancer.

#### Ingredient(s) - State Regulations

asphalt, petroleum California - Proposition 65 calcium carbonate Pennsylvania - Workplace Hazard glass fibers California - Proposition 65 silica, quartz New Jersey - Workplace Hazard Pennsylvania - Workplace Hazard California - Proposition 65 Massachusetts - Hazardous Substance

## **Canadian Regulatory Information**

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR. WHMIS Classification: Not classified or controlled.



Page 5 of 5


# BHM100PS - MOD. PLUS G100 P/S

#### 15. Regulatory Information - Continued

#### Ingredient(s) - Canadian Regulatory Information

silica, quartz

WHMIS - Ingredient Disclosure List



16. Other Information

<u>Revision/Preparer Information</u> This MSDS Supersedes A Previous MSDS Dated: 09/10/2011

### Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

#### HENRY COMPANY

L Printed Using MSDS Generator™ 2000